



TECHNOCEL®

Product:

Functional cellulose fibre for road construction.

Character	Value	Unit
Appearance	<ul style="list-style-type: none"> • long grey fibre 	
Cellulose content	<ul style="list-style-type: none"> • approx. 75 	%
Bulk density	<ul style="list-style-type: none"> • approx. 25 	g/l
Loss on drying	<ul style="list-style-type: none"> • approx. .6 	%
pH-value	<ul style="list-style-type: none"> • approx. 7 	
Ø Fibre length	approx. 1100	µm
Ø Fibre diameter	approx. 45	µm
Sieve analysis (Alpine Air Draught Sieve)		
less than 200 µm	<ul style="list-style-type: none"> • approx. 50 	%
less than 32 µm	<ul style="list-style-type: none"> • approx. 15 	%

Application

TECHNOCEL® natural fibres are non toxic and physically harmless. They are produced from natural resources.

TECHNOCEL® is vital for the production of Stone Mastic Asphalt (SMA), Drain Asphalt and other high quality asphalt products.

The data given on this sheet is based on test results believed to be representative of the product and should not be interpreted as a binding specification.

Richard Baker Harrison Ltd.
253 Cranbrook Road
Ilford, Essex.
IG1 4TQ
U.K.



GB94/3715

Tel : +44 (0)20 8554 0102
Telefax : +44 (0)20 8554 9282
E-mail : rbhltd@aol.com
www : rbhltd.com